

PRODUCTSHEET

26.20020 - BFM SS T316L Spigot Ø100

vlint.

info@vlint.nl | 088 88 77 111 | www.vlint.nl



Product no.	26.20020
Description	BFM SS T316L Spigot Ø100
Brand	BFM
Series	BFM
Type	Spigot

BFM Adapter, Stainless Steel

The BFM Adapter forms the basis of the BFM snap-in system and provides a safe, hygienic and reliable connection between pipework and a BFM connector. The adapters are available in T304L, T316L and C22 Hastelloy and replace traditional connections using hose clamps. Thanks to their precise dimensions, they create a 100% dust- and leak-free connection that is easy to maintain.

What does the BFM Adapter do in practice?

The adapter is fitted to the installation and forms the fixing point for a BFM connector. Thanks to its precise fit, the connection remains reliably sealed, preventing leaks, product loss and product build-up. The connection can also be opened and closed quickly, reducing maintenance time.

The tapered design makes it easy to connect the adapter to existing pipework. The tail can be shortened as needed for a proper fit.

Key benefits

- Part of the BFM snap-in system.
- 100% dust- and leak-free connection.
- Replaces traditional connections using hose clamps.
- Hygienic design without product build-up.
- Available in T304L, T316L and C22 Hastelloy.
- Easy to install and suitable for adaptation to existing pipework.

Applications

The BFM Adapter is suitable for applications including:

- Food processing industry.
- Pharmaceutical industry.
- Chemical process industry.
- Powder and bulk material transport.
- Product conveying systems and process installations.

Practical information

In applications where static electricity may occur, such as with wood dust, flour or milk powder, the use of a static-conductive strip between the two BFM adapters is recommended. When the connector is fitted with Tool Release (TR), a 6 mm hole must be made in the top edge of the adapter. This allows the Tool Release function to be used to comply with the safety requirements of Article 7.7 of the Dutch Working Conditions Decree (Arbeidsomstandighedenbesluit).

Specifications

Material	Stainless Steel (RVS)	Nominal channel diameter	100 mm
Material quality	Stainless Steel 316 (1.4401)	Working length	89 mm
Surface protection	Other	Insertion length connection 1	0 mm

PRODUCTSHEET

26.20020 - BFM SS T316L Spigot Ø100



Fitting connection	✓	Insertion length connection 2	0 mm
Pipe connection	✓	Insulation thickness	2 mm
Extended	✗		
With pre-assembled seal	✗		
Insulated	✗		
Connection 1	Flange		
Connection 2	Duct end		

Supplier	Itemno.	article description
Nedfilter	26.20020	BFM SS T316L Spigot Ø100

info@vlint.nl | 088 88 77 111 | www.vlint.nl