

PRODUCTSHEET

26.305275 - BFM TR Lock-Out Safety System

vlint.

info@vlint.nl | 088 88 77 111 | www.vlint.nl



Product no.	26.305275
Description	BFM TR Lock-Out Safety System
Brand	BFM
Series	BFM
Type	Accessories and parts

BFM Lock Out Safety System

The BFM Lock Out Safety System is a safety accessory for the BFM snap-in system that allows a connector to be safely and controllably locked during maintenance, inspection or cleaning work. By preventing unwanted release of the connector, the system contributes to a safe working environment and a controlled maintenance process.

What does the Lock Out Safety System do in practice?

During maintenance work, the Lock Out Safety System prevents a connector from being accidentally removed or refitted. This allows work to be carried out safely, without risk of unexpected product flows or unwanted access to the installation.

The system connects to the BFM snap-in system and supports lock-out procedures within production environments where safety and process control are essential.

Key benefits

- Prevents unwanted removal of the connector during maintenance.
- Supports safe lock-out procedures.
- Easy to combine with the BFM snap-in system.
- Contributes to a safe working environment.
- Quick to install and easy to operate.
- Suitable for periodic maintenance and inspections.

Applications

The BFM Lock Out Safety System is suitable for applications including:

- Food processing industry.
- Pharmaceutical industry.
- Chemical industry.
- Powder and bulk processing.
- Installations with the BFM snap-in system.
- Maintenance and inspection work involving lock-out procedures.

Practical information

The Lock Out Safety System is intended as an addition to the BFM snap-in system and supports safe maintenance procedures. Check in advance whether the system is suitable for the connector used, and always follow the applicable safety and lock-out procedures within the installation.

Specifications

Material	Stainless Steel (RVS)	Nominal channel diameter	0 mm
Material quality	Other	Working length	0 mm
Surface protection	Other	Insertion length connection 1	0 mm

PRODUCTSHEET

26.305275 - BFM TR Lock-Out Safety System



Fitting connection	×	Insertion length connection 2	0 mm
Pipe connection	×	Insulation thickness	0 mm
Extended	×		
With pre-assembled seal	×		
Insulated	×		
Connection 1	Other		
Connection 2	Other		

Supplier	Itemno.	article description
Nedfilter	26.305275	BFM TR Lock-Out Safety System

info@vlint.nl | 088 88 77 111 | www.vlint.nl